

KERN FL 200

Universal digital force gauge with graphic-assisted display and integrated load cell



Article codes, product groups & Status information

Model article-code	FL 200
Model-Serie	FL
Assortment	Sauter
Product Type	Force measurement
Product group	Digital force-measuring devices (internal sensor)
Product usage type	Main article
EAN code (Model)	4045761138889
Planned start date	2014-1HJ
Customs tariff number	90248000

Technical data - Primary

Max. Force	250 N
Readability	0.1 N

Technical data - Construction

Dimensions of housing	175×75×30 mm
Material housing	Aluminium
Mounting thread	External thread M6

Technical data - Display

Display type	LCD
Display digit height	8.5 mm
DisplayReverse	Yes

Technical data - Power supply

Power supply	Battery & Power supply
--------------	------------------------

Battery type	NiMH
Operating time (Display off)	10 h
Operating time (Display on)	8 h
Mains adapter/adaptor included	CH;EURO
Protection Class	No protection class

Technical data - Measuring system

Units	N
Tolerance (% from Max.)	0.2%
Force direction	Compression;tension

Technical data - Functions

Hold-Function	Yes
Peak-Function	Yes
Limit value (Min - Max)	Yes
Interface	Analog (0 +/-2V);RS-232 serienmäßig;USB-Device

Technical data - Environmental conditions

Maximum operating temperature	35 °C
Minimum storage temperature	40 °C

Technical data - Packing & Shipping

Dimensions packaging (W×D×H)	260×230×75 mm
Gross weight	1.4 kg
Net weight	0.55 kg
Shipping method	Parcel service

KERN FL 200

Universal digital force gauge with graphic-assisted display and integrated load cell



UN number Ni-MH (UN 3496, Packing Instruction #0, Not Restricted as per Special Provision A199)

Packaging component - by weight - cardboard 871 g

Delivery time 1 d

Technical data - Counting data

Memory Yes

Value memory - number of groups 1

Value memory - number of cells (per group) 500

Optional Services

DAkkS calibration - push/pull 963-361

DAkkS calibration - push only 963-261

DAkkS calibration - pull only 963-161

Functions

Standard



Option

